

12 **EUROPEAN PATENT APPLICATION**

21 Application number: 86201363.8

22 Date of filing: 04.08.86

51 Int. Cl.³: **H 01 Q 9/04**
H 01 Q 13/24, H 01 Q 19/06
H 01 Q 19/13

30 Priority: 08.08.85 GB 8519900

43 Date of publication of application:
08.04.87 Bulletin 87/15

88 Date of deferred publication of search report: 13.07.88

84 Designated Contracting States:
DE FR GB IT NL

71 Applicant: The Secretary of State for Defence in Her
Britannic Majesty's Government of the United Kingdom
of Great Britain and
Northern Ireland Whitehall
London SW1A 2HB(GB)

72 Inventor: Backhouse, Paul Michael
31 Sandpiper Crescent
Malvern Worcester, WR14 1UY(GB)

72 Inventor: Apsley, Norman
Mill Brook 76 Albert Road South
Malvern Worcester, WR14 3DX(GB)


72 Inventor: Rees, Huw David
27 Wyke Wane
Malvern Worcester(GB)

74 Representative: Beckham, Robert William et al,
Procurement Executive Ministry of Defence Patents
1A(4), Room 2014
Empress State Building Lillie Road London SW6 1TR(GB)

54 **Microstrip antenna device.**

57 An antenna device 10 comprises a dielectric sheet substrate 16 having an antenna patch 12 on one surface 14 and a ground plane 18 on the other surface 20. A hemispherical dielectric lens 22 is arranged over the antenna patch 12 in intimate contact with it. The substrate 16 and the lens 22 are of low and high permittivity material respectively. The lens 22 couples the antenna patch radiation away from the substrate 16. This avoids the inefficiency arising from power trapping in the substrate of a prior art microstrip patch antenna. The antenna device 10 radiates into a comparatively narrow cone axially perpendicular to the antenna patch 12, and coupling of radiation from a power source of free space can theoretically be 100%. The antenna impedance is a function of its structural geometry, and is easily designed for impedance matching to a power source.

Fig. 1.





European Patent
Office

EUROPEAN SEARCH REPORT

0217426
Application Number

EP 86 20 1363

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
Y	ELECTRONICS LETTERS, vol. 21, no. 8, 11th April 1985, pages 356-357, C.M. HALL et al.: "Microstrip planar arrays with dielectric sphere overlays" * Whole document *	1-3,7,9	H 01 Q 9/04 H 01 Q 13/24 H 01 Q 19/06 H 01 Q 19/13
Y	IEEE TRANSACTIONS ON ANTENNAS AND PROPAGATION, vol. AP-30, no. 2, March 1982, pages 314-318, IEEE, New York; I.J. BAHL et al.: "Design of microstrip antennas covered with a dielectric layer" * Whole document *	1-3,7,9	
A	EP-A-0 117 017 (HAZELTINE)		
D,A	ELECTRONICS LETTERS, vol. 17, no. 20, 1st October 1981, pages 729-731; C.R. BREWITT-TAYLOR et al.: "Planar antennas on a dielectric surface"		
			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			H 01 Q
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		23-02-1988	CHAIX DE LAVARENE C.F.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

(12) **EUROPEAN PATENT APPLICATION**

(21) Application number: 86201363.8

(51) Int. Cl.⁴: **H 01 Q 9/04**
H 01 Q 19/06, H 01 Q 19/13

(22) Date of filing: 04.08.86

(30) Priority: 08.08.85 GB 8519900

(43) Date of publication of application:
08.04.87 Bulletin 87/15

(84) Designated Contracting States:
DE FR GB IT NL

(71) Applicant: **The Secretary of State for Defence in Her
Britannic Majesty's Government of the United Kingdom
of Great Britain and
Northern Ireland Whitehall
London SW1A 2HB(GB)**

(72) Inventor: **Backhouse, Paul Michael
31 Sandpiper Crescent
Malvern Worcester, WR14 1UY(GB)**

(72) Inventor: **Apsley, Norman
Mill Brook 76 Albert Road South
Malvern Worcester, WR14 3DX(GB)**

(72) Inventor: **Rees, Huw David
27 Wyke Wane
Malvern Worcester(GB)**

(74) Representative: **Beckham, Robert William et al,
Procurement Executive Ministry of Defence Patents
1A(4), Room 2014
Empress State Building Lillie Road London SW6 1TR(GB)**

(54) **Microstrip antenna device.**

(57) An antenna device 10 comprises a dielectric sheet substrate 16 having an antenna patch 12 on one surface 14 and a ground plane 18 on the other surface 20. A hemispherical dielectric lens 22 is arranged over the antenna patch 12 in intimate contact with it. The substrate 16 and the lens 22 are of low and high permittivity material respectively. The lens 22 couples the antenna patch radiation away from the substrate 16. This avoids the inefficiency arising from power trapping in the substrate of a prior art microstrip patch antenna. The antenna device 10 radiates into a comparatively narrow cone axially perpendicular to the antenna patch 12, and coupling of radiation from a power source to free space can theoretically be 100%. The antenna impedance is a function of its structural geometry, and is easily designed for impedance matching to a power source.

TITLE 0217426

see front page

ANTENNA DEVICE

This invention relates to an antenna device of the kind used to radiate the output of an electromagnetic power source into free space.

05

Antenna devices are known. These include wire antennae and waveguide horns. An antenna is driven by a power source via an impedance matching network. The network is required because typical solid state power sources such as Gunn or impatt diodes have impedances much lower than that of a wire antenna or waveguide horn. The matching network is not incorporated monolithically in the solid state power source structure since this is not necessarily technically feasible and is wasteful of valuable semiconductor material in any event.

10

Antenna devices are accordingly usually of hybrid form. However, the reactance of the power source is then a function of bond wire connections and the like. The result is that solid state power sources require individual manual adjustment. At higher frequencies in particular, matching requires the use of waveguide cavities which are heavy and bulky relative to the power source or antenna. Moreover, the required degree of mismatch reduction reduces power amplifier bandwidth.

15

20

25

30

35

To avoid the need for an impedance matching network, microstrip patch antennae have been developed. Such an antenna typically consists of a planar rectangular patch of metal on one surface of a dielectric substrate sheet, the other surface bearing a ground plane. The antenna impedance can be arranged to allow a power source to be integrated directly into the antenna structure without an intervening matching network. However, it is found that radiative efficiency is low and bandwidth severely limited for such an antenna as compared to conventional types. Radiative efficiency is low because much of the energy radiated by a patch antenna of known kind is trapped within the substrate layer, and only a small proportion is radiated into free space. Similar effects have been analysed by Brewitt-Taylor, Gunton and Rees in Electronics Letters, 1st Oct 1981, Vol 17, pp 729-731.

It is an object of the invention to provide an alternative form of antenna device.

The present invention provides an antenna device including:-

05

- (1) a conducting antenna patch spaced apart from a ground plane by at least one low loss dielectric element;
- (2) means for energising the antenna patch; and
- (3) a dielectric coupling member having a dielectric constant greater than that of the dielectric element and arranged over the antenna patch to couple radiation therefrom away from the dielectric element.

10

The term "ground plane" is herein employed in accordance with its ordinary signification in the art as meaning a normally but not necessarily flat conducting sheet for earthing purposes.

15

It has been discovered that the invention provides an antenna device capable of coupling power from a source to free space with higher efficiency than a prior art microstrip patch antenna device. In particular, radiation trapping in the dielectric sheet is avoided. In addition, as will be described, the invention is characterised by design geometry features such as dielectric sheet thickness which can easily be selected to provide impedance matching of the antenna device to a power source. There is therefore no need for a matching network. The invention accordingly provides the efficiency of conventional wire antennae, waveguide horns and matching networks combined with the ease of construction of prior art microstrip patch antennae.

20

25

-3-

In a preferred embodiment, the antennae device is arranged to be at or above quarter wavelength resonance; the means for energising the patch antenna comprises a power source connected to one longitudinal end of the patch. In this embodiment, the device may have a dielectric coupling member in the form of a lens. This provides an antenna radiation pattern substantially in the form of a relatively narrow cone centred on the antenna boresight, which is particularly advantageous in use.

The antenna patch may conveniently be a planar and rectangular metal element. The said at least one dielectric element may be a plurality of elements, but is conveniently a single sheet of low loss material. It may be plastics material of dielectric constant in the region of 2.5. The dielectric coupling member preferably has a dielectric constant of more than twice, and preferably at least three times that of the sheet, and may be of alumina with dielectric constant 9.8. The means for energising the antenna patch may be a discrete solid state device arranged between the ground plane and patch and accommodated within the dielectric sheet. Such means may alternatively be a coaxial power connection made through a hole in the ground plane and passing via the dielectric sheet.

The dielectric sheet may be of high resistivity and hence low loss semiconductor material into which a solid state power source is integrated. The semiconductor material may be Si, in which case the coupling member may be barium nona-titanate with a dielectric constant of 36.

-3-

The antenna device may be provided with focussing means to produce a parallel output beam. Alternatively, the dielectric coupling member may have a tapering cross-section suitable for launching radiation into a waveguide.

05

The antenna device of the invention may be arranged with other like devices to form an array.

10 In order that the invention might be more fully understood, embodiments thereof will now be described, by way of example only, with reference to the accompanying drawings, in which:-

Figure 1 schematically shows an antenna device of the invention;

15 Figures 2 and 3 are side and plan views of part of the Figure 1 device illustrating power source provision;

Figure 4 illustrates a coaxial power connection for the Figure 1 device;

Figures 5 and 6 provide impedance data as a function of

20 frequency for the Figure 1 device;

Figure 7 provides measured output radiation patterns for the Figure 1 device with power fed to one end of the antenna patch;

Figure 8 illustrates the radiation pattern arising from a coaxial power connection;

25 Figure 9 provides theoretical radiation patterns for a device of the invention with power fed to one end of the antenna patch;

Figure 10 illustrates the measured radiation pattern obtained from a device of the invention when

30 power is fed to the centre of the antenna patch;

Figure 11 schematically shows an antenna device of the invention appropriate for forming part of an array;

Figures 12 and 13 illustrate parallel output beam production from a device of the invention; and
Figure 14 illustrates use of the invention to launch radiation into a waveguide.

05

Referring to Figure 1, there is shown a sectional view of an antenna device of the invention indicated generally by 10. The device consists of a planar and rectangular metal conductor or antenna patch 12 arranged horizontally on one surface 14 of a dielectric sheet substrate 16. The width dimension of the patch 12 is perpendicular to the plane of the drawing. A metal ground plane 18 is disposed on the other surface 20 of the substrate 16. The substrate 16 is of proprietary material designated "Plastikard", and manufactured by Slater's Plastikard Ltd, a British Company. It has low loss and low permittivity. The substrate 16 may alternatively be of polytetrafluorethylene (PTFE) of dielectric constant 2.1. A hemispherical dielectric lens 22 having a curved surface 24 is arranged over and in intimate contact with the antenna patch 12. The lens 22 is of alumina having a dielectric constant of 9.8. A microwave power source indicated generally by 26 is connected between the patch 12 and ground plane 18 through the substrate 16, as will be described later in more detail.

The antenna device 10 operates as follows. Since the lens 22 is of higher dielectric constant than the substrate 16, radiation from the antenna patch 12 is coupled predominantly into the lens 22 away from the substrate 16. Moreover, the lens 22 has a focussing effect which directs the radiation as a beam into free space beyond the surface 24. The result is that power from the source 26 is radiated into free space with greater efficiency than is possible with a prior art microstrip patch antenna, since power is predominantly coupled away from the substrate 16 to which radiation is lost in the prior art.

0217426

Referring now to Figures 2 and 3, in which parts previously mentioned are like referenced, there are shown respectively side and plan elevations of parts of the device 10 illustrating power source mounting. As illustrated, the substrate 16 has a hole 30 to
05 accommodate a discrete solid state power source 26 such as a Gunn diode or an impatt diode. The diode power source 26 is provided with DC bias relative to the ground plane 18 via a connection 32 to the antenna patch 12.

10 The dielectric sheet substrate 16 may be of low loss semiconductor material such as Si or GaAs into which a solid state power source 26 is integrated. For a substrate of Si with a dielectric constant of 12, an associated dielectric member or lens 22 of barium nona-titanate may be employed having a dielectric constant of 36.

15 Referring now to Figure 4, in which parts previously mentioned are like referenced, there is illustrated power coupling or current feed to the antenna patch 12 via a coaxial line 40. The line 40 extends vertically, ie perpendicular to the plane of the patch 12. It passes
20 through a hole 42 in the ground plane 18 and thence via the dielectric substrate 16 to the patch 12.

Impedance measurements have been made on the antenna device 10 as a function of drive position or power source connection point along the
25 length of the antenna patch 12. Measurements were made using a coaxial feed as shown in Figure 4 together with a network analyser. It has been found surprisingly that the condition for resonance is that the effective antenna length from the drive point is one quarter of a wavelength (or multiples thereof) at the interface between the two
30 dielectrics 16 and 22. Moreover, the current in the antenna patch 12 runs outwards, ie away from the drive point in both directions along the patch. This is quite different to the situation in prior art patch antennae, in which current runs unidirectionally from one end to the other and resonance occurs at an effective antenna length of one
35 half of a wavelength irrespective of drive position.

0217426

Referring now to Figures 5 and 6, there are shown respectively measurements of conductance and susceptance in milli-siemens (ms) plotted against frequency in GHz for an antenna device of the invention. The measurements were made on a device generally similar to that described earlier with reference to Figures 1 and 4, except that the hemispherical lens 22 was replaced by an alumina lens having a focal plane in which the antenna patch was located. Radiation passing through the lens was absorbed in water providing a non-reflecting lossy load. This avoids reflection back to the patch. The patch itself had a length of 3.5mm and a width of 1mm, and was connected at one end to a power source. The thickness h of the dielectric sheet between patch and ground plane was 0.54mm. It can be seen that antenna resonance occurs at about 9.1GHz. Further measurements (not illustrated) on antenna devices of the invention with different values of h indicate that resonant impedance varies linearly with h for h much less than a quarter of a wavelength. Impedance is expected to be a maximum when h is approximately a quarter of a wavelength, the impedance then having a value determined by antenna patch dimensions and the dielectric constants of the two adjacent media.

It can be seen from Figures 5 and 6 that the resonant antenna device impedance is only a few ohms. In particular, the reciprocal of the maximum measured conductance of about 400ms at 9.1GHz is 2.5ohms. Moreover, as has been said, the resonant impedance can be altered by varying h, antenna dimensions and media dielectric constants. Since typical power source impedances are also of the order of a few ohms, it is straightforward to design antenna devices of the invention for impedance matching to power sources.

Referring now to Figure 7, there are shown graphs 50 and 52 in polar coordinates of power (arbitrary units) radiated by an antenna device of the invention plotted as a function of angle. The graphs 50 and 52 relate to the E and H planes respectively, and extend upwardly of the plane of a corresponding horizontal antenna patch such as 12 in Figure 1. The Figure 7 data were obtained at 8GHz using an arrangement generally similar to that of Figure 1 with the vertical current feed shown in Figure 4. Detail differences are as follows. A hemispherical lens similar to 22 was employed, but it was of a commercially available material designated PT9.8 and manufactured by Marconi Electronic Devices Ltd, a British company. The lens curved surface had an antireflection coating. The antenna patch was 5mm in length, and power connection was made at one end. It can be seen that radiation is directed into a comparatively narrow cone for both graphs 50 and 52. Graph 50 is asymmetric due to the effect of the antenna patch current feed which also radiates. Detection of this effect in the H-plane is avoided, because H-plane contributions from the current feed and antenna patch are polarised orthogonally to one another and can be detected separately.

Referring now to Figure 8, there is shown a graph of radiated power as a function of angle in polar coordinates for a current feed to an antenna patch. The patch was 4mm long, power connection was made to one end and measurements were made at 7GHz in the H-plane. As has been mentioned, the H-plane current feed radiation is detectable independently of that from the antenna patch. The graph consists of two lobes 60a and 60b arranged substantially symmetrically about the vertical or boresight direction. The E-plane equivalent of the right-hand lobe 60b becomes combined with the antenna patch E-plane radiation to produce the asymmetry shown in graph 50 in Figure 7.

-9-

The E-plane equivalent of the left-hand lobe 60a is much weaker because of the blocking effect of the antenna patch, and does not make a significant contribution to the graph 50.

05 Referring now to Figure 9, there is shown a theoretical radiation pattern for an antenna device of the invention. The pattern is calculated for a device as shown in Figure 1 operating at 9.8 GHz, and to which power is fed at one end of the antenna patch. The device parameters employed were antenna patch length 5mm, substrate thickness
10 (h) 0.86mm, and lens and substrate dielectric constants 10 and 2.5 respectively. The pattern includes an E-plane graph 70 (solid line) and an H-plane te graph 72 (broken line). Graph 74 shows the H-plane tm pattern (chain line). The calculated antenna radiation pattern indicates output into a comparatively narrow cone in agreement with
15 the measurements discussed previously. It will be noted that the antenna radiation pattern intensity is zero in the (horizontal) plane of the antenna patch.

Referring now to Figure 10, there is shown a further radiation pattern
20 illustrating the effect of power connection to the centre of an antenna patch of the invention. Power measurement was carried out at 8GHz in the E-plane using an antenna patch 10mm in length. The radiation pattern consists of two narrow lobes 80a and 80b arranged fairly symmetrically about boresight, at which there is a null. The
25 null occurs since currents run outwards from the power connection point at the centre of the antenna patch, and the two ends of the patch are radiating in antiphase. This is quite different to conventional microstrip patch antennae, in which currents run along the patch independently of the power connection position.

30

35

-9-

Referring now to Figures 11 to 14 inclusive, there are schematically illustrated various implementations of antenna devices of the invention each similar to that shown in Figure 1. In Figure 11, an antenna device 90 is shown arranged to radiate into free space. The device 90 may be used either alone or accompanied by equivalent devices (indicated by chain lines 92) to form an array. In Figure 12, a device 94 is shown furnished with an additional dielectric lens 96 of concavo-convex form. The lens 96 has an inner concave surface 98 complementary to and in contact with the lens 100 of the device 94. The lenses 98 and 100 form a multiple component lens which produces a parallel output beam from the device 94 as indicated at 102.

As shown in Figure 13, the device output 104 may alternatively be rendered parallel using a mirror 106.

Figure 14 shows a sectional view of an antenna device 110 arranged as a launcher to input radiation to a waveguide 112. In this embodiment the device 10 has a tapering dielectric coupling member 114 for coupling radiation from the antenna patch to the waveguide. This member 114 replaces the hemispherical lens of earlier embodiments. For a cylindrical waveguide, the cross-section of the coupling member 114 perpendicular to the plane of the drawing is circular. For a rectangular waveguide this section is rectangular.

0217426

In summary, the invention provides an antenna device characterised by ease of construction and impedance matching to a power source, high efficiency and advantageous output radiation pattern. The efficiency of coupling a power source to free space is theoretically 100%. In comparison, a prior art microstrip patch antenna is at best about 70% efficient when a low permittivity dielectric substrate is used for the antenna patch. If a silicon substrate were to be used in order to incorporate within it an integrated power source, the efficiency would fall to around 20%. This is because radiation is trapped in the substrate of the prior art device. This results in power loss to the substrate to a degree varying with substrate dielectric constant. Furthermore, the prior art device is unsuitable for use as a member of an array. Coupling between adjacent devices would occur, because each radiation pattern does not fall to zero in the plane of the antenna patch, unlike the invention. Moreover, coupling via the substrate would occur in a prior art array on a common substrate. In contrast, the invention radiates away from the plane of the antenna patch into a comparatively narrow cone from which a substantially parallel output beam can easily be produced. In addition, a semiconductor antenna patch substrate may be employed and a power source integrated therein. Since radiation output is zero in the plane of the antenna patch, the invention is ideally suited to producing arrays of antenna devices which do not couple together.

Claims:-

1. An antenna device including a conducting antenna patch (12) spaced apart from a ground plane (18) by at least one low loss dielectric element (16) and means (26) for energising the antenna patch (12); characterised in that the antenna device (10) also
5 includes a low-loss dielectric coupling member (22) having a dielectric element (16) and arranged over the antenna patch (12) to couple radiation therefrom away from the dielectric element (16).
2. An antenna device according to Claim 1 characterised in
10 that the dielectric element (16) is in sheet form and bears the antenna patch (12) and ground plane on respective sheet surfaces.
3. An antenna device according to Claim 1 or 2 characterised in that the dielectric coupling member (22) has a dielectric
15 constant at least twice that of the dielectric element (16).
4. An antenna device according to Claim 3 characterised in that the dielectric element (16) is of plastics material and the dielectric coupling member (22) is of ceramic material.
20
5. An antenna device according to claim 3 characterised in that the dielectric element (16) comprises semiconductor material.
6. An antenna device according to Claim 5 characterised in
25 that the means (26) for energising the antenna patch (12) is a solid state device integrated within the dielectric element (16).

7. An antenna device according to any preceding claim characterised in that the means (26) for energising the antenna patch (12) includes a power connection to one end of the antenna patch (12).

5

8. An antenna device according to any preceding claim characterised in that it includes focussing means (96, 106) arranged to provide a parallel beam (102) from the antenna device radiation pattern.

10

9. An antenna device according to any one of claims 1 to 7 characterised in that it is arranged as a member of an array of like devices (90, 92).

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig.6.




Fig.5.





Fig.7.

5mm PATCH ANTENNA DRIVEN AT END
 $h = 0.54\text{mm}$ 8GHz



4/6

0217426

Fig.8.

4mm ANTENNA DRIVEN AT ONE END
7GHz
H-PLANE RADIATION PATTERN DUE TO VERTICAL CURRENT FEED





Fig. 9.



DIELECTRIC CONSTANTS 10 AND 2.5
 PLANAR ANTENNA 5mm IN LENGTH
 $h = 860\mu\text{m}$ FREQUENCY 9.8GHz

Fig. 10.




Fig. 11.




Fig. 12.




Fig. 13.




Fig. 14.

